

BLACKBURN ELECTRIC WIRES

FLEXIBLE CABLES # 4

BETATHERM CABLE

CLASS "F" - 155 DEG. C

<0.75mm² 450/750V - >1mm² .6/1KV

TINNED COPPER CONDUCTOR INSULATED WITH POLY - OLEFIN - COPOLYMER
CROSSED LINKED BY IRRADIATION

C S A mm ²	STRANDING No./mm	AMPS	A W G No.	NOM. DIAM.	AVAILABLE COLOURS
0.25	14/0.15	2	24	1.5mm	0,1,2,4
0.50	16/0.20	5	20	1.9mm	0,1,2,4,6,8
0.75	24/0.20	7.5	18.5	2.2mm	0,1,2,3,4,5,6,7,8,9
1.00	32/0.20	10	17	2.5mm	0,1,2,3,4,5
1.50	30/0.25	15	15	3.1mm	0,1,2,6,7
2.50	50/0.25	20	13	3.5mm	0,1,2,4
4.00	56/0.30	25	11	3.8mm	0,1,2
6.00	84/0.30	40	9.5	4.5mm	0,1,2
10.00	80/0.40	70	7	6.6mm	0
16.00	128/0.40	100	5	7.2mm	0
25.00	196/0.40	200	3	9.5mm	0
35.00	280/0.40	250	2	10.5mm	0

COLOUR CODE: 0 = BLACK, 1 = RED, 2 = WHITE, 3 = BROWN, 4 = BLUE, 5 = YELLOW,
6 = ORANGE, 7 = GREEN/YELLOW, 8 = VIOLET, 9 = PINK

BLACKBURN ELECTRIC WIRES