

PRODUCT DATA SHEET



160 ELECTRICAL TAPE.

Single sided reinforced polyester.

Product Features & Applications:

- * Heavy duty usage in large air and oil filled transformers.
- * Slot edging of Nomex[^] (Dupont registered trademark)
- * Lead and saddle tie-down.
- * Reinforcements.
- * Holding and seperating ground insulation.
- * Bundling motor coils and coil covering.
- * Economical glass cloth replacement. (class 155 deg. C)

Product Specifications:

* Temperature:	155 deg. C
* Backing:	Glass reinforced polyester
* Max width:	1300mm
* Adhesive:	Acrylic thermosetting
* Colour:	Cream
* Backing thickness:	0.165mm
* Total thickness:	0.203mm
* Tensile:	612.5 N/10mm
* Elongation:	6%
* Adhesion to steel:	4.95 N/10mm
* Insulation resistance:	10 ⁴ megohms
* Direct electrolytic corrosion:	1.0
* Dielectric strength:	6500 volts
* Moisture resistance:	Excellent
* Solvent resistance:	Excellent
* Storage stability:	Excellent
* Approvals:	Available on request

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.