## PRODUCT DATA SHEET



## 4150 ELECTRICAL TAPE. Single sided Polyester.

## Product Features & Applications:

- Slot edging.
- Lead anchoring.
- Field coil bundling.
- \* Wrapping.
- \* Harnessing.
- \* Interphase/interlayer insulation.
- Economical.

## Product Specifications:

- \* Temperature:
- \* Backing:
- \* Maxwidth:
- \* Adhesive:
- \* Colour:
- \* Backing thickness:
- \* Total thickness:
- \* Tensile:
- \* Elongation:
- \* Adhesion to steel:
- Insulation resistance:
- \* Direct electrolytic corrosion:
- Dielectric strength:
- Moisture resistance:
- \* Solvent resistance:
- Storage stability:
- \* Approvals:

- 105 deg. C
- Polyester (0.013) laminated with rope fibre
- 1150mm
- Rubber thermosetting
- White (natural)
- 0.089mm
- 0.152mm 66.5 N/10mm
- 4%
- 5.5 N/10mm
- 45 megohms
- 0.9
- 4500 volts
- Excellent
- Verygood
- Good
  - Available on request

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buy er will independently determine the suitability of the product for the buy er's purpose.