

BLACKBURN ELECTRIC WIRES

FLEXIBLE CABLES # 5

SYNTEX CABLE

CLASS "F" - 155°C 3.5KVOLT

TINNED COPPER CONDUCTOR COVERED BY ONE LAYER OF POLYESTER FILM, 1 LAYER OF NOMEX COUNTERWOUND, OVERLAPPING APPROX. 40%, POLYESTER FILAMENT BRAID & THEN POLYURETHANE COATED. AVAILABLE IN WHITE ONLY.

STRANDING No./mm	C S A mm ²	AMPS	A W G No.	NOM. DIAM.	PACKAGING SIZE
50/0.25	2.50	20	13	3.0mm	100MT COIL
56/0.30	4.00	25	11	4.1mm	50MT COIL
84/0.30	6.00	40	9.5	4.9mm	50MT COIL
80/0.40	10.00	70	7	5.8mm	50MT COIL
128/0.40	16.00	100	5	7.0mm	50MT COIL
200/0.40	25.00	200	3	8.8mm	50MT COIL
280/0.40	35.00	250	2	10.2mm	50MT COIL
400/0.40	50.00	300	1/0	12.2mm	25MT COIL
560/0.40	70.00	350	2/0	14.0mm	25MT COIL
483/0.50	95.00	410	3/0	16.2mm	25MT COIL